



## Tile Adhesive & Dry Mix Mortars



Note :This information is based on our test results and may vary from site to site. Hence, trial of product before application is recommended. Changes/Improvements in products are done continually and hence information given above is not binding. There is no express or implied guaranty / warranty for the results. Application surface should be sound and free from oil/grease/paint & such loose contaminates.



## MAESTRO DIAMOND

1) Ready to use, needs only mixing with water. 2) Excellent adhesion, low shrinkage. 3) Excellent water resistance characteristics. 4) Suitable for Indoor and outdoor use. 5) Sufficiently flexible to accommodate Thermal & Physical movements. 6) Needs no curing and soaking of substrate or stones. 7) Packing : 20 Kgs

**Note :** Use hacking or mechanical key on stone surface.

### Features & Benefits

### Technical Information

1) Base : Polymer modified cementitious material. 2) Appearance : Cement Grey/White Powder. 3) Mix ratio : Approx. 3 : 1 (by vol). 4) Open time: Approx. 30 minutes at 30°C. 5) Pot life : Approx. 30-60 minutes at 30°C. 6) Coverage : 40-45 sqft/20Kg bag at 3 mm thickness. 7) Trafficable time : 24 Hours (min.) 8) Internal curing time : 7 days at 30°C



## MAESTRO GOLD

1) Ready to use, needs only mixing with water. 2) Excellent adhesion, low shrinkage. 3) Excellent water resistance characteristics. 4) Suitable for Indoor and outdoor use. 5) Sufficiently flexible to accommodate Thermal & Physical movements. 6) Needs no curing and soaking of substrate or tile. 7) Packing : 20 Kgs

### Features & Benefits

### Technical Information

1) Base: Polymer modified cementitious material. 2) Appearance : Cement Grey/White Powder. 3) Mix ratio : Approx. 3 : 1 (by vol). 4) Open time Approx. 30 minutes at 30°C. 5) Pot life : Approx. 30-60 minutes at 30 °C. 6) Coverage : 40-45 sqft/20Kg bag at 3 mm thickness. 7) Trafficable time : 24 Hours (min.) 8) Internal Curing time : 7 days at 30°C



## MAESTRO SILVER

1) Ready to use, needs only mixing with water. 2) Excellent adhesion, low shrinkage. 3) Excellent water resistance characteristics. 4) Suitable for Indoor and outdoor use. 5) Sufficiently flexible to accommodate Thermal & Physical movements. 6) Needs no curing and soaking of substrate or tile. 7) Packing : 20 Kgs

### Features & Benefits

### Technical Information

1) Base : Polymer modified cementitious material. 2) Appearance : Cement Grey Powder. 3) Mix ratio : Approx. 3 : 1 (by vol). 4) Open time Approx. 30 minutes at 30°C. 5) Pot life : Approx. 30-60 minutes at 30 °C. 6) Coverage : 40-45 sqft/20Kg bag at 3 mm thickness. 7) Trafficable time : 24 Hours (min.) 9) Internal Curing time : 7 days at 30°C

## (GREY/WHITE CEMENT BASED POLYMER MODIFIED STONE FIXING ADHESIVE)

MAESTRO DIAMOND Adhesive is blended polymer modified cement based stone fixing adhesive specially designed for applications like fixing non porous stones, granite. on internal/external horizontal vertical surface. This flexible adhesive also has an excellent water resistance ability. Mechanical clamps is recommended for stones fixed at heights of more than 10 feet or places where vibrations are felt severely. For heavy stone applications technical team may be consulted.

## (GREY/WHITE CEMENT BASED HIGHLY POLYMER MODIFIED TILE FIXING ADHESIVE)

MAESTRO GOLD is blended polymer modified cement based tile adhesive specially designed for applications like fixing Large Format Ceramic, Glazed, Vitrified Tiles. small granite stones on Internal/external horizontal and vertical surfaces. This flexible adhesive also has an excellent water resistance ability.

## (GREY CEMENT BASED POLYMER MODIFIED TILE FIXING ADHESIVE)

MAESTRO SILVER is blended polymer modified cement based tile adhesive specially designed for applications like fixing Ceramic, Glazed, Vitrified Tiles, on Internal horizontal and vertical surface. This adhesive also has an excellent water resistance ability. It is suitable for fixing Ceramic tiles, vitrified tiles, etc. on a new substrate & horizontal tile on tile applications.



### (THREE COMPONENT EPOXY BASED JOINT FILLER/GROUT)

MAESTRO EPOXY JOINT FILLER is Three Component Epoxy Based Joint filler/Grout, specially designed for applications like filling gaps, while installing Ceramic, Glazed, Vitrified Tiles, granite, mosaic on Internal/external horizontal and vertical surface. This joint filler also has an excellent water resistance ability. EPOXY JOINT FILLER is suitable for filling gaps from 2 to 12 mm.

#### Features & Benefits

- 1) Ready to use, needs only mixing.
- 2) Excellent adhesion, No shrinkage.
- 3) Excellent waterproofing characteristics.
- 4) Suitable for Indoor and outdoor use.
- 5) Sufficiently flexible to accommodate Thermal & Physical movements.
- 6) Available in attractive Shades.
- 7) Dust Free & Anti Fungal.
- 8) Packing : 1Kg & 5 Kgs

#### Technical Information

- 1) Base : Three component Epoxy material.
- 2) Appearance : Depends on shade.
- 3) Open time : Approx. 30 minutes at 30°C.
- 4) Pot life : Approx. 45 minutes at 30 °C.
- 5) Coverage : Depends on joint depth & width.
- 6) Trafficable time : 24 Hours (min.)
- 7) Internal curing time : 7 days at 30° C
- 8) Approx Ratio of Resin : Hardener : Filler is 2:1:7.

Note : When using Epoxy for external application color fading/darkening may occur. \*Also available in Sparkle Finish - Gold, Silver and Copper finish in all Shades.



### MAESTRO CEMENTITIOUS JOINT FILLER

### (CEMENT BASED POLYMER MODIFIED JOINT FILLER/GROUT)

MAESTRO JOINT FILLER Is blended polymer modified cement based joint filler/Grout, specially designed for applications like filling gaps, while installing Ceramic, Glazed, Vitrified Tiles, granite, mosaic on Internal/external horizontal and vertical surface. This highly polymer modified Joint filler has an excellent water resistance ability. It is suitable for filling gaps from 1 to 8 mm.

#### Features & Benefits

MAESTRO JOINT FILLER Is blended polymer modified cement based joint filler/Grout, specially designed for applications like filling gaps, while installing Ceramic, Glazed, Vitrified Tiles, granite, mosaic on Internal/external horizontal and vertical surface. This highly polymer modified filler also has an excellent water resistance ability. This is suitable for filling gaps from 1 to 8 mm.

#### Technical Information

- 1)Base : Polymer modified cementitious material.
- 2) Appearance : Depends on shade. Powder form
- 3) Mix ratio : Approx. 3 : 1 (by vol).
- 4) Open time : Approx. 30 minutes at 30°C.
- 5) Pot life : Approx. 30-45 minutes at 30°C.
- 6) Coverage : Depends on Joint depth & Width.
- 7) Trafficable time : 24 Hours (min.)



### MAESTRO BLOCK JOINTING MORTAR

### (GREY CEMENT BASED POLYMER MODIFIED AAC/CLC FIXING ADHESIVE)

MAESTRO BLOCK JOINTING MORTAR is blended polymer modified grey cement based thin adhesive specially designed for applications of fixing AAC/CLC blocks. This highly flexible adhesive also has an excellent water resistance ability.

#### Features & Benefits

- 1) Ready to use, needs only mixing with water.
- 2) Excellent adhesion, No shrinkage.
- 3) Excellent water resistance characteristics.
- 4) Suitable for Indoor and outdoor use.
- 5) Sufficiently flexible to accommodate Thermal & Physical movements.
- 6) Needs no curing and soaking of substrate AAC/CLC block.
- 7) Packing : 40 Kgs

#### Technical Information

- 1) Base : Polymer modified cementitious material.
- 2) Appearance : Cement Grey Powder.
- 3) Mix ratio : Approx. 3 : 1 (by vol).
- 4) Open time : Approx. 30 minutes at 30°C.
- 5) Pot life : Approx. 30-45minutes at 30 °C.
- 6) Coverage : Approx 150 Sq. feet for 40kg. at 3 mm thickness for 600x200x150 MM block size.
- 7) Plastering Time Gap : 48 Hours (min)
- 8) Internal curing time 7 days at 30° C



## (GREY CEMENT BASED READY MIX MORTAR / PLASTER)

MAESTRO READY PLASTER is blended powder cement based ready mix mortar specially designed for applications like plastering & finishing new brick walls/jointing bricks or repairing old plasters conveniently for both internal/external horizontal surface.

### MAESTRO READY PLASTER

### Features & Benefits

1) Ready to use, needs only mixing with water. 2) Excellent adhesion, low shrinkage. 3) Excellent resistance to water absorption. 4) Suitable for Indoor and outdoor use. 5) Better strength compared to site mixed plaster. 6) Needs lesser curing time as compared to site mixed plaster. 7) Minimum rebound loss. Saves labour & time, more productivity. 8) Packing : 40 Kgs.

### Technical Information

1) Base : Polymer modified cementitious material. 2) Ratio of Cement : Sand 1 : 3 (By weight) . 3) Appearance : Cement Grey Powder. 4) Mix ratio : Approx. 5-6 ltr water for 40kg pack. 5) Open time : Approx. 20 minutes at 30°C. 6) Pot life : Approx. 30 minutes at 30 °C. 7) Coverage: 80 sqft/40Kg. bag at 6 mm . thickness. 8) Initial setting time : 24 hrs (min). 9) Water curing required for initial three days.



## SPECIAL ADDMIX LIQUID

Special Addmix Liquid when added to Joint Filler gives more strength & Flexibility.

- Packing 100 ml

### MAESTRO GROUT ADDMIX

Fast acting acid based cleaner for regular cleaning of dirt and stains on tile surfaces, designed for daily maintenance of tiles.



### Features & Benefits


- Ready to Use
- Fast acting
- Easy to use
- Ideal for Interior & Exterior
- Packaging 1 Ltr

### Subtract

- All Ceramic Tile
- Glass Tile
- Vitrified Tile • Glass Mosaic Tile
- Glazed Ceramic Tile • Porcelain Tile
- For interior & exterior applications of Tile surfaces

### MAESTRO TILE CLEANER

NOTE :- Not Recommended For Natural Stones.



### MAESTRO TILE SPACER

## (PVC TILE SPACERS FOR PERFECT GAPS BETWEEN TILES)

Tile Spacers ranging from 2 MM to 10 MM are available for providing accurate gap between Tiles. Helpful in achieving perfect grout finish.

## VAISHALI FLOORINGS PVT. LTD.

Sector 11 F - Sanwer Road, Industrial Area, Indore, (MP) India - 452015  
Help Line No. - + 91 7223090045 E- Mail: dmcc.mp@gmail.com